

SSP Product Update

Product: PV Series Plug Valves

SSP PV Series Plug Valve offering now includes the following additions:

- Factory applied locking hardware and locking hardware kits
- One-piece stainless steel handle
- Downstream pressure venting

These changes are documented on the SSP website and will be added to the next version of the catalog.

Locking Hardware

Locking hardware secures the valve in the open or closed position to protect against accidental actuation.

Features

- Meets OSHA Lockout/Tag out Standard 29 CFR Part 1910.147
- Designed for use with padlock shackle diameters from 1/4 to 5/16 in. (6.4 to 8mm)
- Solid one-piece aluminum construction for easy installation and durability. No special tools or complex mounting instructions.
- Available factory installed or for field installation



Ordering Information

To order locking hardware kits for field installation, select the part number from the table below. The kit will include the locking plate and installation instructions.

Factory installed locking hardware can be added to any size valve by adding **-LD** to the part number.

The price is the same for both factory installed locking hardware and the locking hardware kits for field installation. To calculate the factory installed list price, add the locking hardware kit list price (above) to the list price for the valve.

Examples:

PV4-D6-316-LD

PV6-8PF-LD

One-Piece Stainless Steel Handles

Features

Stainless steel valves featuring a one-piece handle and plug are available for PV Series plug valves. Stainless steel handles are used in higher-temperature applications up to 400°F (204°C) or other severe external conditions.

Ordering Information

To order PV Series Plug Valves with one-piece stainless steel handles, add **-BH1** to the part number. Stainless steel handles are available for both brass and stainless steel valve bodies. To calculate the price of a PV Series plug valve with a stainless steel handle, add the list price from the table below to the list price of the valve.

Examples:

PV4-D6-316-BH1

PV6-8PF-BH1



Vented Valves

PV Series plug valves are now available with a ported body to allow downstream pressure to vent to the atmosphere when the valve is in the closed position. Vented PV Series valves come standard with a red handle.

Note: The pressure rating for vented plug valves is 150 psig (10.3 bar).



Ordering Information

To order PV Series vented plug valves, add a **V** to the valve size designator in the basic part number.

Examples: PV4**V**-D4
PPV6**V**-D6-316

